Office of the Revisor of Statutes Administrative Rules



TITLE: Proposed Expedited Permanent Rules Regulating Adult Changing Stations

AGENCY: Department of Labor and Industry

REVISOR ID: R-4839

MINNESOTA RULES: Chapter 1341

The attached rules are approved for publication in the State Register

Sheree Spor

Sheree Speer Chief Deputy Revisor

| | 03/12/24 | | REVISOR | SS/BM | RD4839 |
|------|--------------------|------------------------------|------------------------|--------------------------|----------------|
| 1.1 | Department | of Labor and Industry | 7 | | |
| 1.2 | Proposed Ex | xpedited Permanent Ru | iles Regulating Adu | ult Changing Statio | ons |
| 1.3 | 1341.0011 | IBC CHAPTER 11. | | | |
| 1.4 | | [For text of subp | arts 1 to 7, see Minn | nesota Rules] | |
| 1.5 | Subp. 8. | IBC section 1109, Oth | er features and fac | ilities. | |
| 1.6 | | [For text of iten | ns A to C, see Minne | esota Rules] | |
| 1.7 | <u>D.</u> | Section 1109.2 is amend | led to add a section t | to read as follows: | |
| 1.8 | <u>1109.2.</u> 4 | Adult-sized changing | stations. Where pro | vided, adult changir | ng stations |
| 1.9 | shall be | accessible. Where requi | red, adult changing | stations shall be acco | essible and |
| 1.10 | shall con | mply with sections 1109 | .2.4.1 through 1109. | 2.4.4. | |
| 1.11 | <u>110</u> | 9.2.4.1 Where required | . At least one adult c | hanging station shal | l be provided |
| 1.12 | in a | ll of the following location | ons: | | |
| 1.13 | | 1. In assembly and mere | cantile occupancies, | where an aggregate of | of six or more |
| 1.14 | | male and female water | closets are required. | In buildings of mixe | d occupancy, |
| 1.15 | | only those water closets | required for the asse | embly and mercantile | e occupancies |
| 1.16 | | shall be used to determ | ine the adult changing | ng station requireme | <u>nt.</u> |
| 1.17 | | 2. In Group B occupand | eies providing educat | tional facilities for st | udents above |
| 1.18 | | the 12th grade, where a | n aggregate of twelv | ve or more male and | female water |
| 1.19 | | closets are required to s | serve the classrooms | and lecture halls. | |
| 1.20 | | 3. In Group E occupance | ies, where a room or | space used for assem | bly purposes |
| 1.21 | | requires an aggregate o | f six or more male a | nd female water clo | sets for that |
| 1.22 | | room or space. | | | |
| 1.23 | | 4. In Minnesota Depart | ment of Transportat | ion rest areas provid | ed with |
| 1.24 | | plumbing and electricit | y at toileting locatio | <u>ns.</u> | |

| | 03/12/24 | REVISOR SS/BM RD4839 |
|------|----------|---|
| 2.1 | | 5. State park campgrounds provided with plumbing and electricity at toileting |
| 2.2 | | locations. |
| 2.3 | | 6. State park visitor centers provided with plumbing and electricity at toileting |
| 2.4 | | locations. |
| 2.5 | | 7. In hospitals and ambulatory care facilities, where an aggregate of six or |
| 2.6 | | more male and female water closets are required. |
| 2.7 | | 8. In Group B outpatient clinics, where an aggregate of six or more male and |
| 2.8 | | female water closets are required. |
| 2.9 | | 1109.2.4.2 Room. Adult changing stations shall be located in toilet rooms that |
| 2.10 | | include only one water closet and only one lavatory. Fixtures located in such rooms |
| 2.11 | | shall be included in determining the number of fixtures provided in an occupancy. |
| 2.12 | | The occupants shall have access to the required adult changing station at all times |
| 2.13 | | that the associated occupancy is occupied. |
| 2.14 | | Exception: Adult changing stations shall be permitted to be located in family |
| 2.15 | | or assisted-use toilet rooms required in Section 1109.2.1. |
| 2.16 | | 1109.2.4.3 Prohibited location. The accessible route from public and employee |
| 2.17 | | toilet rooms required by Minnesota Rules, chapter 1305, to an accessible adult |
| 2.18 | | changing station shall not require travel through security checkpoints. |
| 2.19 | | 1109.2.4.4 Travel distance. The adult changing station shall be located on an |
| 2.20 | | accessible route and the path of travel to the facility shall not exceed 1000 feet. |
| 2.21 | | Exception: In Group A-4 and A-5 occupancies the path of travel shall not |
| 2.22 | | exceed 2,000 feet. |
| 2.23 | | D. E. Section 1109.3, Sinks, is amended by deleting the exception. |

| | 03/12/24 | REVISOR | SS/BM | RD4839 |
|------|--|---------------------------|--------------------------|-------------|
| 3.1 | E. F. Section 1109.4, Kitcher | ns and kitchenettes, is a | amended by adding an | exception |
| 3.2 | to read as follows: | | | |
| 3.3 | Exception: Where multiple kitch | ens are provided in a | space or room, at lea | st one |
| 3.4 | kitchen shall be accessible. | | | |
| 3.5 | F. <u>G.</u> Section 1109.7 is ame | nded to read as follow | /s: | |
| 3.6 | 1109.7 Elevators. Passenger elevators | on an accessible route | e shall be accessible a | nd comply |
| 3.7 | with Minnesota Rules, chapter 1307, | Minnesota Elevators | and Related Devices. | |
| 3.8 | G. <u>H.</u> Section 1109.8 is ame | ended to read as follow | WS: | |
| 3.9 | 1109.8 Lifts. Platform (wheelchair) li | fts are permitted to be | e a part of a required a | accessible |
| 3.10 | route in new construction where indica | ated in items 1 to 10. | Platform (wheelchair) | lifts shall |
| 3.11 | be accessible and comply with Minne | sota Rules, chapter 13 | 307, Minnesota Eleva | tors and |
| 3.12 | Related Devices. | | | |
| 3.13 | 1. An accessible route to a perfor | ming area and speake | er platforms. | |
| 3.14 | 2. An accessible route to wheelch | nair spaces required to | o comply with the wh | eelchair |
| 3.15 | space dispersion requirements of | Sections 1108.2.2 to | 1108.2.6 or the access | sible route |
| 3.16 | requirements of Sections 1104.4. | 3 and 1104.4.4. | | |
| 3.17 | 3. An accessible route to spaces the | at are not open to the | general public with ar | occupant |
| 3.18 | load of not more than five. | | | |
| 3.19 | 4. An accessible route within a d | welling or sleeping u | nit. | |
| 3.20 | 5. An accessible route to jury box | xes and witness stand | s; raised courtroom st | ations |
| 3.21 | including judges' benches, clerks' | stations, bailiffs' stati | ons, deputy clerks' sta | tions, and |
| 3.22 | court reporters' stations; and to de | epressed areas such a | s the well of the court | - |
| 3.23 | 6. An accessible route to load and | d unload areas serving | g amusement rides. | |

| | 03/12/24 | REVISOR | SS/BM | RD4839 |
|------|--|-------------------------|--------------------------|----------------|
| 4.1 | 7. An accessible route to play con | mponents or soft co | ntained play structur | res. |
| 4.2 | 8. An accessible route to team or | player seating area | s serving areas of sp | ort activity. |
| 4.3 | 9. An accessible route where exis | sting exterior site co | onstraints make use o | of a ramp or |
| 4.4 | elevator infeasible. | | | |
| 4.5 | 10. An accessible route within a | tenant space as requ | uired in Section 1104 | .5 where the |
| 4.6 | area accessed by the lift has an oc | ccupant load of 150 | maximum or where | the structural |
| 4.7 | limitations make use of an elevat | or impracticable. | | |
| 4.8 | H. <u>I.</u> Section 1109.10 is amo | ended to read as fol | lows: | |
| 4.9 | 1109.10 Detectable warnings. Passer | nger transit platform | n edges bordering a o | drop-off and |
| 4.10 | not protected by platform screens or g | uards and circulation | n paths that cross trac | eks shall have |
| 4.11 | a detectable warning. | | | |
| 4.12 | Exception: Detectable warnings | are not required at | bus stops. | |
| 4.13 | H.J. Section 1109.12.3 is an | nended to read as fo | llows: | |
| 4.14 | 1109.12.3 Point of sale and serv | vice counters. When | re counters are provi | ded for sales |
| 4.15 | or distribution of goods or service | es, at least one of eac | h type provided in ea | ach area shall |
| 4.16 | be accessible. Where such counter | ers are dispersed thr | oughout the building | g or facility, |
| 4.17 | accessible counters shall also be | dispersed. | | |
| 4.18 | J. <u>K.</u> Section 1109.14, Fuel | dispensing systems | , is deleted in its enti | irety. |
| 4.19 | K.L. Section 1109, Other for | eatures and facilities | s, is amended by add | ling four |
| 4.20 | sections to read as follows: | | | |
| 4.21 | 1109.16 Automatic teller and fare v | ending machines. | Where automatic tell | ler and fare |
| 4.22 | vending machines are provided, at lea | st one machine at e | ach location shall be | e accessible. |
| 4.23 | Where bins are provided for envelope | es, wastepaper, or ot | her purposes, at leas | t one of each |
| 4.24 | type shall be accessible. | | | |

1341.0011

RD4839

| 5.1 | 1109.17 Public telephones. Where coin | -operated public pay telephones, coinless public |
|--------------|---|--|
| 5.2 | pay telephones, public closed-circuit tele | ephones, courtesy telephones, or other types of |
| 5.3 | public telephones are provided, public te | elephones shall be provided in accordance with |
| 5.4 | Section 1109.17 for each type of public t | telephone provided. For purposes of this section, a |
| 5.5 | bank of telephones shall be considered t | wo or more adjacent telephones. For purposes of |
| 5.6 | this section, "public building" means a b | uilding or portion of a building constructed by, on |
| 5.7 | behalf of, or for the use of the state of M | linnesota or any local government and any |
| 5.8 | department, agency, public school distric | et, special purpose district, or other instrumentality |
| 5.9 | of the state or local government. | |
| 5.10 | 1109.17.1 Wheelchair accessible to | elephones. Where public telephones are provided, |
| 5.11 | telephones complying with ICC A1 | 17.1 shall be provided in accordance with Table |
| 5.12 | 1109.17.1. | |
| 5.13 | Exception: Drive-up only publ | lic telephones. |
| 5.14 | ТАВ | BLE 1109.17.1 |
| 5.15 | WHEELCHAIR AG | CCESSIBLE TELEPHONES |
| 5.16 5.17 | Number of Telephones Provided on a Floor, Level, or Exterior Site | Minimum Required Number of Wheelchair Accessible Telephones |
| 5.18 | 1 or more single units | 1 per floor, level, and exterior site |
| 5.19 | 1 bank | 1 per floor, level, and exterior site |
| 5.20 | 2 or more banks | 1 per bank |
| 5.21 | 1109.17.2 Volume controls. All publ | ic telephones shall have volume controls complying |
| 5.22 | with ICC A117.1. | |
| 5 22 | 1100 17 3 TTVs TTVs complying | with ICC A117.1 shall be provided in accordance |
| 5.23 | with Section 1109.17.3. | with ICC ATT 7.1 shall be provided in accordance |
| 5.24 | with Section 1107.17.3. | |

| | 03/12/24 | REVISOR SS/BM RD4839 | | | | |
|------|----------|--|--|--|--|--|
| 6.1 | | 1109.17.3.1 Bank requirement. Where four or more public pay telephones are | | | | |
| 6.2 | | provided at a bank of telephones, at least one public TTY complying with ICC | | | | |
| 6.3 | | A117.1 shall be provided at that bank. | | | | |
| 6.4 | | Exception: TTYs shall not be required at banks of telephones located within | | | | |
| 6.5 | | 200 feet (61 m) of, and on the same floor as, a bank containing a public TTY. | | | | |
| 6.6 | | 1109.17.3.2 Floor requirement. TTYs in public buildings shall be provided in | | | | |
| 6.7 | | accordance with Section 1109.17.3.2.1. TTYs in private buildings shall be provided | | | | |
| 6.8 | | in accordance with Section 1109.16.3.2.2. | | | | |
| 6.9 | | 1109.17.3.2.1 Public buildings. Where at least one public pay telephone is | | | | |
| 6.10 | | provided on a floor of a public building, at least one public TTY shall be | | | | |
| 6.11 | | provided on that floor. | | | | |
| 6.12 | | 1109.17.3.2.2 Private buildings. Where four or more public pay | | | | |
| 6.13 | | telephones are provided on a floor of a private building, at least one public | | | | |
| 6.14 | | TTY shall be provided on that floor. | | | | |
| 6.15 | | 1109.17.3.3 Building requirement. TTYs in public buildings shall be provided | | | | |
| 6.16 | | in accordance with Section 1109.17.3.3.1. TTYs in private buildings shall be | | | | |
| 6.17 | | provided in accordance with Section 1109.17.3.3.2. | | | | |
| 6.18 | | 1109.17.3.3.1 Public buildings. Where at least one public pay telephone is | | | | |
| 6.19 | | provided in a public building, at least one public TTY shall be provided in | | | | |
| 6.20 | | the building. | | | | |
| 6.21 | | 1109.17.3.3.2 Private buildings. Where four or more public pay telephones | | | | |
| 6.22 | | are provided in a private building, at least one public TTY shall be provided | | | | |
| 6.23 | | in the building. | | | | |

| | 03/12/24 | REVISOR SS/BM RD4839 |
|------|----------|---|
| 7.1 | | 1109.17.3.4 Exterior site requirement. Where four or more public pay telephones |
| 7.2 | | are provided on an exterior site, at least one public TTY shall be provided on the |
| 7.3 | | site. |
| 7.4 | | 1109.17.3.5 Rest stops, emergency roadside stops, and service plazas. Where |
| 7.5 | | a public pay telephone is provided at a public rest stop, emergency roadside stop, |
| 7.6 | | or service plaza, at least one public TTY shall be provided. |
| 7.7 | | 1109.17.3.6 Hospitals. Where a public pay telephone is provided serving a hospital |
| 7.8 | | emergency room, hospital recovery room, or hospital waiting room, at least one |
| 7.9 | | public TTY shall be provided at each location. |
| 7.10 | | 1109.17.3.7 Transportation facilities. In addition to the requirements of Sections |
| 7.11 | | 1109.17.3.1 to 1109.17.3.4, in transportation facilities, where one public pay |
| 7.12 | | telephone serves a particular entrance to a bus or rail facility, a TTY shall be |
| 7.13 | | provided to serve that entrance. In airports, in addition to the requirements of |
| 7.14 | | Sections 1109.17.3.1 to 1109.17.3.4, if four or more public pay telephones are |
| 7.15 | | located in a terminal outside the security areas, a concourse within the security |
| 7.16 | | areas, or a baggage claim area in a terminal, at least one public TTY shall also be |
| 7.17 | | provided in each location. |
| 7.18 | | 1109.17.3.8 Detention and correctional facilities. In detention and correctional |
| 7.19 | | facilities, where a public pay telephone is provided in a secured area used only by |
| 7.20 | | detainees or inmates and security personnel, then at least one TTY shall be provided |
| 7.21 | | in at least one secured area. |
| 7.22 | 110 | 9.17.4 Shelves for portable TTYs. Where a bank of telephones in the interior of |
| 7.23 | a bi | ailding consists of three or more public pay telephones, at least one public pay |
| 7.24 | tele | phone at the bank shall be provided with a shelf and an electrical outlet in accordance |
| 7.25 | wit | n ICC A117.1. |

03/12/24

REVISOR

| 8.1 | Exceptions: |
|------|--|
| 8.2 | 1. Secured areas of detention and correctional facilities where shelves and outlets |
| 8.3 | are prohibited for purposes of security or safety shall not be required to comply |
| 8.4 | with Section 1109.17.4. |
| 8.5 | 2. The shelf and electrical outlet shall not be required at a bank of telephones with |
| 8.6 | a TTY. |
| 8.7 | 1109.18 Airplane hangars. An accessible route and accessible entrance shall be provided |
| 8.8 | to 5 percent of all airplane hangars in a facility, but not less than one hangar used for the |
| 8.9 | storage or repair of private aircraft. |
| 8.10 | 1109.19 Two-way communication systems. Where a two-way communication system is |
| 8.11 | provided to gain admittance to a building or facility or to restricted areas within a building |
| 8.12 | or facility, the system shall comply with ICC A117.1. |
| 8.13 | [For text of subparts 8a to 13, see Minnesota Rules] |
| 8.14 | 1341.0603 A117.1 SECTION 603, TOILET AND BATHING ROOMS. |
| 8.15 | Subpart 1. [Repealed, 39 SR 95] |
| 8.16 | Subp. 1a. Section 603.2.2 Door swing. A117.1 section 603.2.2, exception 2 is amended |
| 8.17 | to read as follows: |
| 8.18 | 2. Where the room is intended for individual use, including family or assisted use, and a |
| 8.19 | clear floor space complying with Section 305.3 is provided within the room beyond the arc |
| 8.20 | of the door swing, the door shall not be required to comply with Section 603.2.2. |
| 8.21 | [For text of subpart 2, see Minnesota Rules] |
| 8.22 | 1341.0613 A117.1 SECTION 613, ADULT CHANGING STATIONS. |
| 8.23 | A117.1 chapter 6 is amended by adding a section and subsections to read as follows: |

| | 03/12/24 | REVISOR | SS/BM | RD4839 |
|--------------|---|--------------------------------------|------------------------|---------------|
| 9.1 | | SECTION 613 | | |
| 9.2 | ADUL | T CHANGING STATI | ONS | |
| 9.3 | 613.1 General. Adult changing st | ations shall comply with | Section 613.2 throu | ıgh 613.4. |
| 9.4 | 613.2 Installation location. When | re required, adult changi | ng stations shall be i | installed in |
| 9.5 | accordance with the locations spec | ified in Section 613.2.1. | Where not required b | ut provided, |
| 9.6 | adult changing stations shall be ins | talled in accordance with | the locations specifi | ed in section |
| 9.7 | <u>613.2.1 or 613.2.2.</u> | | | |
| 9.8 | 613.2.1 Single-user or famil | y or assisted-use toilet | room. Where adult | changing |
| 9.9 | stations are required in an acc | cessible toilet room with | only one water clos | et and one |
| 9.10 | lavatory, or in a family or ass | isted-use toilet room, the | e room shall provide | all of the |
| 9.11 | following components: | | | |
| 9.12 | 1. A dispenser for soap c | complying with Section 3 | <u>308.</u> | |
| 9.13 | 2. A hand towel dispense | er or hand dryer complyi | ing with Table 603.6 | ÷ |
| 9.14 | 3. A coat hook located in | a close proximity to the o | changing surface. | |
| 9.15 | 4. A waste receptacle. | | | |
| 9.16 | 5. Signage indicating "A | dult Changing Station" p | provided at the entra | nce to the |
| 9.17 | room and complying wit | h the tactile and visual c | haracter requirement | ts in Section |
| 9.18 | <u>703.2.</u> | | | |
| 9.19 | 6. Signage indicating the | weight capacity and ins | structions for operati | on of the |
| 9.20 | changing station within t | he room. | | |
| 9.21 | 613.2.2 Room or space othe | <mark>r than a toilet room.</mark> W | here adult changing | stations are |
| 9.22 | provided in a room or space of | | | |
| 9.23 | nurses' work areas, therapist | | 1 | |
| 9.24 9.25 | changing station shall be loca following components: | acu in a compartment or | 100111 mat metudes | |
| | | | | |

| | 03/12/24 | REVISOR | SS/BM | RD4839 |
|-------|------------|---|------------------------|---------------|
| 10.1 | | 1. Privacy provided by walls, curtains, or partitic | ons. | |
| 10.2 | | 2. A turning space complying with Section 304. | | |
| 10.3 | | 3. A lavatory complying with Section 606 or an | alcohol-based hand | sanitizer |
| 10.4 | | dispenser. | | |
| 10.5 | | 4. Where a lavatory is provided in the compartm | ent or room, provide | e a dispenser |
| 10.6 | | for soap. | | |
| 10.7 | | 5. Where a lavatory is provided in the compartme | nt or room, provide | a hand towel |
| 10.8 | | dispenser or hand dryer complying with Table 60 |)3.6. | |
| 10.9 | | 6. A waste receptacle. | | |
| 10.10 | <u>613</u> | .3 Room clearances. An adult changing station a | nd its supporting str | ucture when |
| 10.11 | in th | ne operational position shall not obstruct required | clear floor spaces an | d clearances |
| 10.12 | at a | ccessible elements, maneuvering clearances at do | ors or at the wheelch | nair turning |
| 10.13 | spac | ces. | | |
| 10.14 | | Exception: The turning spaces shall be permitted | d to include a toe cle | earance of 9 |
| 10.15 | | inches (227 mm) minimum above the floor and s | shall extend 6 inches | s (152 mm) |
| 10.16 | | maximum below the table, measured from the fin | nished edge of the ta | uble surface |
| 10.17 | | when the provided adult changing station is in th | e lowest operational | l position. |
| 10.18 | <u>613</u> | .4 Changing surface. A changing surface shall be | provided and shall | comply with |
| 10.19 | Sec | tion 613.4. | | |
| 10.20 | <u>613</u> | .4.1 Safety and performance. Adult changing sta | ations shall comply | with the |
| 10.21 | foll | owing safety and performance requirements: | | |
| 10.22 | | 1. Protect the user from falling from the changing | g surface along the o | open long |
| 10.23 | | sides by means such as retractable safety rails the | at comply with secti | on 613.4.5. |

| | 03/12/24 | R | EVISOR | SS/BM | RD4839 |
|-------|------------|--|------------------------|-----------------------|-----------------|
| 11.1 | | 2. Support a weight of not less that | an 400 lbs. (182 kg) | applied to the chan | ging |
| 11.2 | | surface. | | | |
| 11.3 | | 3. Be anchored in place in accordan | nce with section 903. | .6, where the adult c | hanging |
| 11.4 | | station is required by section 613. | .2.1. | | |
| 11.5 | | 4. Provide a changing surface that | t is smooth, non-abs | orbent, and resistan | it to |
| 11.6 | | corrosion. | | | |
| 11.7 | | 5. Where electrical components are | e provided, they shall | comply with the M | innesota |
| 11.8 | | Electrical Code. | | | |
| 11.9 | | 6. Where operable controls are pro- | ovided for adult cha | nging stations requ | ired by |
| 11.10 | | section 613.2.1, they shall comply | y with Section 309.4 | <u>.</u> | |
| 11.11 | <u>613</u> | .4.2 Size. The changing surface sha | all be 70 inches (177 | 78 mm) minimum i | n length |
| 11.12 | and | 30 inches (762 mm) minimum in v | width. | | |
| 11.13 | <u>613</u> | .4.3 Height adjustability. The chan | ging surface height s | hall be adjustable at | variable |
| 11.14 | heig | ghts from 17 inches (432 mm) mini | imum to 38 inches (9 | 965 mm) maximum | 1 above |
| 11.15 | the | floor as measured to the top of the | changing surface. | | |
| 11.16 | | Exceptions: | | | |
| 11.17 | | 1. Where the adult changing station | on is required, a fixe | d-height changing | surface |
| 11.18 | | shall be permitted with the approv | val of the administra | tive authority in loc | cations |
| 11.19 | | where the applicant provides docu | umentation of prior i | ncidents of vandali | sm. The |
| 11.20 | | fixed-height changing surface sha | Ill be mounted with t | the top 19 inches (4 | . <u>83 mm)</u> |
| 11.21 | | minimum and 23 inches (584 mm | ı) maximum above tl | he floor. | |
| 11.22 | | 2. Where the adult changing static | on is provided but no | ot required by IBC | Section |
| 11.23 | | 1109.2.4.1, a fixed-height changing | g surface shall be per | mitted and shall be r | nounted |

| | 03/12/24 | | REVISOR | SS/BM | RD4839 |
|-------|------------|------------------------------|-------------------------------|--------------------------|--------------|
| 12.1 | | with the top of the changin | g surface 19 inches (| 483mm) minimum and | 1 23 inches |
| 12.2 | | (584mm) maximum above | the floor. | | |
| 12.3 | <u>613</u> | .4.4 Clearances. Clearances | s complying with Sect | tions 613.4.4.1 and 613 | .4.4.2 shall |
| 12.4 | be p | provided adjacent to the cha | nging surface, measu | red when the surface i | s in the |
| 12.5 | oper | rational position. | | | |
| 12.6 | | 613.4.4.1 Side clearance. | A 36-inch (914mm) d | eep minimum side clea | trance shall |
| 12.7 | | be provided along the oper | n long side of the cha | nging surface. | |
| 12.8 | | Exception: In the rais | ed position, the side | rail shall be permitted | to overlap |
| 12.9 | | the side clearance. | | | |
| 12.10 | | 613.4.4.2 End clearance. | A 36-inch (914mm) v | vide minimum end clea | trance shall |
| 12.11 | | be provided along the dept | h of one end of the cl | hanging surface. The v | vidth of the |
| 12.12 | | end clearance shall extend t | he depth of the chang | ing surface and the side | e clearance. |
| 12.13 | | Exceptions: | | | |
| 12.14 | | 1. A 24-inch (610mm) | wide minimum end c | elearance shall be perm | itted where |
| 12.15 | | a clear floor space con | nplying with Section | 305.3 is provided with | in the room |
| 12.16 | | beyond the clearances | for the changing sur | face. | |
| 12.17 | | 2. Where installed in l | ocations specified in | Section 613.2.2, end c | learances |
| 12.18 | | complying with Section | on 613.4.4.2 are not r | equired. | |
| 12.19 | <u>613</u> | .4.5 Side rail. Where side r | ails are provided at th | ne changing surface the | ey shall |
| 12.20 | com | pply with Sections 613.4.5.1 | and 613.4.5.2. | | |
| 12.21 | | 613.4.5.1 Size and locatio | n. Side rails shall be | a minimum of 2/3 of th | e length of |
| 12.22 | | the changing surface and s | hall be centered +/- 3 | inches (75mm) along | the long |
| 12.23 | | open sides of the changing | surface. | | |

| | 03/12/24 | REVISOR | SS/BM RD4839 |
|-------|------------------|---|--|
| 13.1 | <u>61</u> | 3.4.5.2 Rail positioning. Side rails shall be c | capable of being raised and lowered |
| 13.2 | Th | e side rail shall be fixed in place when in the | e raised position. The top of the side |
| 13.3 | rai | l shall extend 5 inches (127mm) minimum ab | pove the top of the changing surface. |
| 13.4 | <u>1341.0902</u> | A117.1 SECTION 902, DINING SURFA | ACES AND WORK SURFACES. |
| 13.5 | <u>A117.1</u> | section 902.1, exception 2, is amended to r | read as follows: |
| 13.6 | <u>902.1 (</u> | General. Accessible dining surfaces and worl | k surfaces shall comply with Section |
| 13.7 | <u>902.</u> | | |
| 13.8 | Ex | cceptions: | |
| 13.9 | <u>1.</u> | Dining surfaces and work surfaces primarily | for children's use shall be permitted |
| 13.10 | to | comply with Section 902.5. | |
| 13.11 | <u>2.</u> | Adult changing surfaces shall not be require | ed to comply with this section. |